

MATERIAL SAFETY DATA SHEET

ISSUE No. 12 JUNE 2005

PAGE 1 of 2



Spring Road, Ibstock Leicestershire LE67 6LR UK

Phone: +44 (0) 1530 261145 fax:+44(0) 1530 262801

Email: enquiries@garryson.co.uk www.garryson.com

1. IDENTIFICATION OF PRODUCT			
MOUNTED POINTS			
2. COMPOSITION / INFORMATION ON INGREDIENTS			
Chemical Identity	% By Weight	CAS No.	MEL / OES (mg/m ³)
Aluminium Oxide	40 - 60	1344 - 28 - 1	(Total inhalable dust) 10
			(Total respirable dust) 5
Vitrified Bond	40 - 60	-----	10
3. HEALTH HAZARDS DATA			
ACUTE EXPOSURE : Dust may cause irritation and abrasion to eyes and may irritate respiratory system. CHRONIC EXPOSURE : Long term over exposure to dust may cause lung damage with symptoms of shortness of breath and diminished breathing capacity. Chronic effects may be irritated by smoking. Prolonged exposure to high noise levels may adversely affect hearing. A greater risk is likely from materials being worked on, paints, coatings etc. Therefore an assessment of the substances being abraded by the product is essential, prior to use. CARCINOGENICITY : None of the components are known to be carcinogenic.			
4. FIRST AID			
INHALATION : Inhaling dust may irritate the respiratory system. If this occurs, remove person to fresh air. If irritation persists, seek medical assistance. EYE CONTACT : Dust may irritate eyes. If this occurs, flush eyes out thoroughly with water. If irritation persists, seek medical assistance. SKIN CONTACT : Dust may irritate skin. If this occurs, wash thoroughly with soap and water. If used incorrectly, products may abrade the skin. If this occurs, thoroughly clean wound and apply a sterile dressing. INGESTION : If significant quantities of dust are ingested, seek medical assistance.			
5. FIRE AND EXPLOSION			
FLAMMABILITY : Not flammable EXTINGUISHING MEDIA : N/A SPECIAL FIRE FIGHTING PROCEDURES : N/A HAZARDOUS COMBUSTION PRODUCTS : N/A			
6. ACCIDENTAL RELEASE			
No special measures required.			
7. HANDLING AND STORAGE REQUIREMENTS			
Avoid dropping or impact.			
8. EXPOSURE CONTROLS / PERSONAL PROTECTION			
VENTILATION : Use local exhaust ventilation as required to ensure exposure to dust levels does not exceed MEL or OES. If LEV is not available a suitable respirator or dust mask should be worn. GLOVES : Heavy duty cloth or leather gloves recommended. EYE PROTECTION ; Safety goggles or full face shield should be worn.			
9. PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE : Various shapes of shank mounted vitrified bond containing abrasive material.. BOILING POINT : N/A MELTING POINT : N/A SPECIFIC GRAVITY : N/A VAPOUR PRESSURE : N/A VAPOUR DENSITY : N/A EVAPORATION RATE : N/A SOLUBILITY IN WATER : Insoluble.			

MOUNTED POINTS

10. STABILITY AND REACTIVITY DATA

STABILITY : Stable

REACTIVITY / INCOMPATIBILITY: Avoid contact with strong acids or oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS : None

HAZARDOUS POLYMERISATION ; Will not occur.

11. TOXICOLOGICAL DATA

No toxicity data known for these products.

12. ECOLOGICAL DATA

No ecological data available for these products.

13. DISPOSAL

Dispose of so as to comply with applicable local regulations.

14. TRANSPORTATION DATA

These products are not regulated for transportation purposes.

15. ENVIRONMENTAL REGULATORY DATA**16. OTHER INFORMATION**

No known regulatory requirements.

The preceding information is believed to be correct and current as of the date of preparation of this Material Safety Data Sheet. Since the use of this information and the conditions of use of these products are not within the control of ATI Garryson Limited, it is the user's obligation to assure safe working conditions.